

TX-5050W40FC180-NUVENG-A03

PRODUCT SPECIFICATION

Features:

- ◆Excellent transiting heat from LED chip operating under 2.5A.
- ◆High luminous output.
- ◆No UV.
- ◆Encapsulated materials are environmentally certified and meet environmental requirements.

Chip Material:

- ◆ThinGaN

Emitting Color:


- ◆White

Applications:


- ◆Auxiliary lighting
- ◆Ambient lighting
- ◆Architectural lighting

| | | | | | |
|----------|----------------------------|----------|------------|------|--------|
| Part No. | TX-5050W40FC180-NUVENG-A03 | Spec No. | WKF-BE0739 | Page | 1 of 9 |
|----------|----------------------------|----------|------------|------|--------|


Package Dimensions:




Top view




Side view



Bottom view



Recommended solder pad



Recommended stencil pattern

Notes:

- 1.All dimensions are in millimeters .
- 2.Tolerances unless otherwise mentioned are ± 0.1 mm .

| | | | | | |
|----------|----------------------------|----------|------------|------|--------|
| Part No. | TX-5050W40FC180-NUVENG-A03 | Spec No. | WKF-BE0739 | Page | 2 of 9 |
|----------|----------------------------|----------|------------|------|--------|

Absolute Maximum Ratings (Tc=25°C)

| Parameter | Symbol | Ratings | Unit |
|---|--------|------------------------------------|------|
| Forward Current | IF | 2500 | mA |
| Reverse Voltage | VR | Not designed for reverse operation | V |
| Power Dissipation | PD | 37.5 | W |
| Junction Temperature | Tj | 150 | °C |
| Electrostatic Discharge Threshold (ESD) | ESD | 2000 | V |
| Storage Temperature | Tstg | -40~+70 | °C |
| Operation Temperature | Topr | -30~+100 | |

Notes:

- Specifications are subject to change without notice.
- The data on this specification is for reference only and the actual data is in accordance with the acknowledgment.
- Precautions for ESD:
STATIC SHIELD Electricity and surge damages the LED. It is recommended to use a wrist band or anti-electrostatic glove when handling the LED. All devices, equipment and machinery must be properly grounded.

Electrical Optical Characteristics (Tc=25°C)

| Parameter | Symbol | Condition | Emitting color | Min. | Typ. | Max. | Units |
|-------------------------------------|-----------------|-----------|----------------|------|------|------|---------|
| Luminous Flux | ϕ_v | If=2.5A | W | 2000 | 2250 | 2500 | lm |
| Forward Voltage | V_f | | W1/W2/W3/W4 | 3.0 | 3.4 | 3.8 | V |
| Viewing Angle at 50% IV | $2\theta_{1/2}$ | | W | — | 120 | — | Deg |
| Correlated Colour Temperature | CCT | If=1.0A | W | 6500 | 6750 | 7000 | K |
| | | If=2.5A | W | 6900 | 7250 | 7500 | |
| Reverse Current | I_R | — | W | — | — | — | μA |
| Thermal Resistance Junction to Case | $R\theta_{J-C}$ | — | W | — | 3.4 | — | K/W |
| Temperature Coefficient of Voltage | $V\Delta F/T$ | If=2.5A | W | — | -2.1 | — | mV/°C |


Notes:

- 1.Luminous intensity is measured with a light sensor and filter combination that approximates the CIE eye-response curve.
2. $\theta_{1/2}$ is the off-axis angle at which the luminous intensity is half the axial luminous intensity.
- 3.Luminous flux measurement tolerance:±15%.
- 4.Forward voltage measurement tolerance:±0.15V.


Typical Electrical/Optical Characteristics Curves

(25°C Ambient Temperature Unless Otherwise Noted)


Forward Current VS. Forward Voltage




Forward Current VS. Luminous flux





Temperature VS. Relative color temperature (IF=2500mA)



Temperature VS. Relative Luminous Flux (IF=2500mA)





Notes:

1. $2\theta\ 1/2$ is the off axis angle from lamp centerline where the luminous intensity is 1/2 of the peak value.
2. View angle tolerance is $\pm 5^\circ$.

| | | | | |
|----------|----------------------------|----------|------------|-------------|
| Part No. | TX-5050W40FC180-NUVENG-A03 | Spec No. | WKF-BE0739 | Page 7 of 9 |
|----------|----------------------------|----------|------------|-------------|

Usage Precautions


Storage Environment Condition

Temperature: 5°C ~ 30°C (41°F ~ 86°F)

Humidity: 60% RH Max.

Soldering Condition

Use the conditions shown to the under figure.





| Profile Feature | Lead-Based Solder |
|---|-------------------|
| Average Ramp-Up Rate (Tsmax to Tp) | 3°C/second max. |
| Preheat: Temperature Min (Tsmin) | 100°C |
| Preheat: Temperature Max (Tsmax) | 150°C |
| Preheat: Time (Tsmin to Tsmax) | 60-120 seconds |
| Time Maintained Above: Temperature (Tl) | 183°C |
| Time Maintained Above: Time (tL) | 60-150 seconds |
| Peak/Classification Temperature (Tp) | 225°C |
| Time Within 5°C of Actual Peak Temperature (Tp) | 10-30 seconds |
| Ramp-Down Rate | 6°C/second max. |
| Time 25°C to Peak Temperature | 6 minutes max. |

Note:

All temperatures refer to topside of the package, measured on the package body surface.

Dimensions For Cannulation And Packaging

Quantity:500PCS



Notes:

1. All dimensions are in millimeters.
2. Tolerances are ± 2.0 mm unless otherwise noted.
3. The products are packaged together with silica gel, Transport, not to the weight of welding LED light-emitting area, As a result of the weight of LED light-emitting zone in the quality of, Irresponsible of the Company.

| | | | | | |
|----------|----------------------------|----------|------------|------|--------|
| Part No. | TX-5050W40FC180-NUVENG-A03 | Spec No. | WKF-BE0739 | Page | 9 of 9 |
|----------|----------------------------|----------|------------|------|--------|