

# TX-H1935SW17C-2860V36-03H95

## PRODUCT SPECIFICATION

**Features:**

- ◆Excellent transiting heat from LED chip operating under 1600mA.
- ◆Provide uniform cross distribution of positive white and warm white dual color scheme, mixed pure.
- ◆High luminous output.
- ◆No UV.
- ◆Encapsulated materials are environmentally certified and meet environmental requirements.

**Chip Material:**

- ◆GaInN

**Emitting Color:**


- ◆White
- ◆Warm white

**Applications:**

- ◆Commercial lighting
- ◆General Lighting

Part No.	TX-H1935SW17C-2860V36-03H95	Spec No.	WKF-BF0376	Page	1 of 10
----------	-----------------------------	----------	------------	------	---------

**Package Dimensions:**



I: Warm white ; II: White

**Notes:**

- 1.All dimensions are in millimeters .
- 2.Tolerances unless otherwise mentioned are  $\pm 0.25\text{mm}$  .

**Code Formats:**

TX-H1935SW17C-2860V36-03H95

TX	—	H	19	35	SW	17	C	—	2860	V36	—	03	H95
TYANSHINE	—	high density	series	watt typ	performance	LES	texture	—	CCT	VOLTs	—	BOM	Ra

Part No.	TX-H1935SW17C-2860V36-03H95	Spec No.	WKF-BF0376	Page	2 of 10
----------	-----------------------------	----------	------------	------	---------

**Absolute Maximum Ratings**

Parameter	Symbol	Ratings	Unit	
Forward Current	IF	1600	mA	
Reverse Voltage	VR	Not designed for reverse operation	V	
Power Dissipation	PD	W	57	W
		S	57	
		S+W	57	
Junction Temperature	Tj	W	135	°C
		S	135	
Case Temperature (C)	Tc	85	°C	
Electrostatic Discharge Threshold (ESD)	ESD	2000	V	
Storage Temperature	Tstg	-30~+100	°C	
Operation Temperature	Topr	-30~+80		

**Notes:**

- Specifications are subject to change without notice.
- The data on this specification is for reference only and the actual data is in accordance with the acknowledgment.
- Precautions for ESD:  
STATIC SHIELD Electricity and surge damages the LED. It is recommended to use a wrist band or anti-electrostatic glove when handling the LED. All devices, equipment and machinery must be properly grounded.

**Electrical Optical Characteristics (Tc=25°C)**



Parameter	Symbol	Condition	Emitting color	Min.	Typ.	Max.	Units
Luminous Flux	$\phi_v$	If=1050mA	S	—	2600	—	lm
			W	—	3400	—	
Forward Voltage	$V_f$		S	33	35	37	V
			W	33	35	37	
Correlated Colour Temperature	CCT		S	—	2800	—	K
			W	—	6000	—	
Viewing Angle at 50% IV	$2\theta_{1/2}$		S	—	115	—	Deg
			W	—	115	—	
Reverse Current	$I_R$		$\Delta$	—	—	—	$\mu A$
Thermal Resistance Junction to Case	$R\theta_{J-C}$			—	—	0.5	—
Temperature Coefficient of Voltage	$V\Delta F/T$	S	—	-13.2	—	mV/°C	
		W	—	-13.2	—		
Color Rendering Index	Ra	S	—	95	—	—	
		W	—	95	—		



**Notes:**



- 1.Luminous intensity is measured with a light sensor and filter combination that approximates the CIE eye-response curve.
2. $\theta_{1/2}$  is the off-axis angle at which the luminous intensity is half the axial luminous intensity.
- 3.Luminous flux measurement tolerance:±15%.
- 4.Forward voltage measurement tolerance:±3%.
- 5.Ra measurement tolerance: ±2.



## Typical Electrical/Optical Characteristics Curves

(25°C Ambient Temperature Unless Otherwise Noted)










**Notes:**

1.  $2\theta_{1/2}$  is the off axis angle from lamp centerline where the luminous intensity is 1/2 of the peak value.
2. View angle tolerance is  $\pm 5^\circ$ .



**Chromaticity Coordinates (Condition: IF=1050mA, Tc=25°C)**



**Notes:**


1.chromaticity (x, y) measurements tolerance: ±0.005.

**Reliability Test**

Test Item	Test Condition
Continuous Operation Test	IF=1050mA Ta=25°C ×1000hrs
Low Temperature Storage Test	-30°C × 1000 hours
High Temperature Storage Test	100 °C × 1000 hours
Moisture-proof Test	85 °C, 85 %RH for 500 hours
Thermal Shock Test	-40 °C × 15 minutes – 125 °C × 15 minutes, 100 cycle

**Dimensions For Cannulation And Packaging**

**Quantity: 36PCS**



**Notes:**

1. All dimensions are in millimeters.
2. Tolerances are  $\pm 2.0$  mm unless otherwise noted.
3. The products are packaged together with silica gel, Transport, not to the weight of welding LED light-emitting area, As a result of the weight of LED light-emitting zone in the quality of, Irresponsible of the Company.

Part No.	TX-H1935SW17C-2860V36-03H95	Spec No.	WKF-BF0376	Page	10 of 10
----------	-----------------------------	----------	------------	------	----------