

TX-5490W90FSA15-NU3CD-02

PRODUCT SPECIFICATION

Features:

- ◆Excellent transiting heat from LED chip operating under 1900mA.
- ◆Ceramic eutectic package allows it to have minimal internal stress and excellent thermal path.
- ◆Flip chip coated with package, the output of lumen is stable.
- ◆High luminous output.
- ◆Encapsulated materials are environmentally certified and meet environmental requirements.

Chip Material:

- ◆GaN

Emitting Color:


- ◆Cold white

Applications:

- ◆Automobile lighting

Part No.	TX-5490W90FSA15-NU3CD-02	Spec No.	WKF-ER0002	Page	1 of 8
----------	--------------------------	----------	------------	------	--------


Package Dimensions:



Top view

Side view

Bottom view



Recommended solder pad

recommended stencil pattern

Notes:

- 1.All dimensions are in millimeters .
- 2.Tolerances unless otherwise mentioned are $\pm 0.1\text{mm}$.

Part No.	TX-5490W90FSA15-NU3CD-02	Spec No.	WKF-ER0002	Page	2 of 8
----------	--------------------------	----------	------------	------	--------

Absolute Maximum Ratings (Tc=25℃)

Parameter	Symbol		Ratings	Unit
Forward Current	IF	W1	1900	mA
		W2	1900	
Reverse Voltage	VR		Not designed for reverse operation	V
Power Dissipation	PD		90	W
Junction Temperature	Tj		150	℃
Electrostatic Discharge Threshold (ESD)	ESD		2000	V
Storage Temperature	Tstg		-40~+70	℃
Operation Temperature	Topr		-30~+125	

Notes:

1.Specifications are subject to change without notice.

2.The data on this specification is for reference only and the actual data is in accordance with the acknowledgment.

3.Precautions for ESD:

STATIC SHIELD Electricity and surge damages the LED. It is recommended to use a wrist band or anti-electrostatic glove when handling the LED. All devices, equipment and machinery must be properly grounded.

Electrical Optical Characteristics (Tc=25°C)

Parameter	Symbol	Condition	Emitting color	Min.	Typ.	Max.	Units
Luminous Flux	Φ_v	If=1500mA	W1	8500	9300	9800	lm
			W2	1700	1850	2000	
Forward Voltage	V_f		W1	45	46.5	48	V
			W2	9.0	9.3	9.6	
Correlated Colour Temperature	CCT	If=200mA	W1	6300	6800	7200	K
Viewing Angle at 50 % IV	$2\theta_{1/2}$	—	W1	—	120	—	Deg
			W2	—	120	—	
Reverse Current	I_R	—	W1	—	—	—	μA
			W2	—	—	—	
Thermal Resistance Junction to Case	$R\theta_{J-C}$	If=1500mA	—	—	0.36	—	K/W
Temperature Coefficient of Voltage	$V\Delta F/T$		—	—	-2.8	—	mV/℃

Notes:


- 1.Luminous intensity is measured with a light sensor and filter combination that approximates the CIE eye-response curve.
2. $\theta_{1/2}$ is the off-axis angle at which the luminous intensity is half the axial luminous intensity.
- 3.The dominant wavelength (λ_d) is derived from the CIE chromaticity diagram and represents the single wavelength which defines the color of the device.
- 4.Luminous flux measurement tolerance:±15%.
- 5.Forward voltage measurement tolerance:±0.15V.

Part No.	TX-5490W90FSA15-NU3CD-02	Spec No.	WKF-ER0002	Page	4 of 8
----------	--------------------------	----------	------------	------	--------


Typical Electrical/Optical Characteristics Curves



(25°C Ambient Temperature Unless Otherwise Noted)



Forward Current VS. Forward Voltage



Forward Current VS. Luminous flux







Notes:

- 1. 2θ 1/2 is the off axis angle from lamp centerline where the luminous intensity is 1/2 of the peak value.
- 2. View angle tolerance is ± 5°.


Usage Precautions

Storage Environment Condition

Temperature: 5°C ~ 30°C (41°F ~ 86°F)

Humidity: 60% RH Max.

Soldering Condition



Profil-Charakteristik Profile Feature	Symbol	Pb-Free(SnAgCu)Assembly			Einheit Unit
		Minimum	Recommendation	Maximum	
Ramp-up Rate to Preheat 25°C to 150°C	-	-	2	3	K/s
Time t_s T_{Smin} to T_{Smax}	t_s	60	100	120	s
Ramp-up Rate to Peak T_{Smax} to T_p	-	-	2	3	K/s
Liquidus Temperature	T_L	217			°C
Time above Liquidus temperature	t_L	-	80	100	s
Peak Temperature	T_P	-	245	260	°C
Time within 5°C of the specified peak temperature T_p -5 K	t_P	10	20	30	s
Ramp-down Rate T_p to 100°C	-	-	3	6	K/s
Time 25°C to T_p	-	-	-	480	-

Note:

All temperatures refer to topside of the package, measured on the package body surface.